




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 1/04, 1/02	A1	(11) International Publication Number: WO 98/25388 (43) International Publication Date: 11 June 1998 (11.06.98)
(21) International Application Number: PCT/IB97/01444 (22) International Filing Date: 17 November 1997 (17.11.97) (30) Priority Data: 96402658.7 6 December 1996 (06.12.96) EP (34) Countries for which the regional or international application was filed: AT et al. (71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventor: MEYER, Axel, Eugenio; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: SCHOONHEIJM, Harry, B.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: TELEPHONE**(57) Abstract**

A telephone comprises a housing with a plurality of coverable control keys at the front and a cover that can be moved between a closed position in which said control keys are covered and an open position in which the control keys are accessible for operation. If desired, the cover and the housing can include an angle of approximately 90° in this position, so that the telephone can be put on a table or on another flat surface in an upright position. In addition to being pivotable, the cover is movable parallel to the housing between the closed position and a moved intermediate position, from which intermediate position the cover can be pivoted to the open position.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Telephone

Description

The invention relates to a telephone with a housing that comprises a plurality of coverable control keys at the front and a cover movable between a closed position in which said control keys are covered and an open position in which the cover is
5 flapped down around a pivot axis near to an edge of the housing, in which open position said control keys are accessible for operation.

Telephones of this type are known in various embodiments (EP 0 492 748 A2; Japanese published patent application 3-244182). The microphone of the telephone is known to be accommodated in the flap-down flap. The flap has for its object to minimize the
10 dimensions of the telephone during the time the telephone is not used. It further has for its object to provide a protection of the control keys which cannot be depressed inadvertently due to the presence of the flap and in closed position of the flap.

A drawback of telephones of above type is that the flap is relatively vulnerable also in closed position. The flap is pivoted exclusively along an edge of the
15 housing. The length of the flap in said known telephones is larger than the width of the flap, so that a relatively large lever arm is present for forces exerted near to the free end of the flap. Another drawback is that minor forces are already sufficient to open the flap, that is, partly, so that the flap is easily caught on an object, for example when the telephone is put away in the inside pocket of a piece of garment or in a bag.

20 It is an object of the invention to provide a telephone of the type defined in the opening paragraph for which the flap is less vulnerable and catches less easily on an object and is characterized in that the flap can be moved parallel to the housing between said closed position and an intermediate position and in that the cover can be pivoted around said pivot axis between the intermediate position and the open position. It is observed that slidable
25 flaps on telephones are known per se (DE 4307 164 A1). Such flaps that can only slide, however, have the drawback that the flap in open position cannot be used as a support or base for putting the telephone upright on the table or another suitable underground.

An embodiment of the telephone according to the invention which makes a firm attachment of the cover to the housing of the telephone possible is characterized in

that the cover in closed position comprises a main portion positioned substantially parallel to the front of the housing, and also side portions contiguous with the main portion near to the side edges, which side portions in closed position are located adjacent housing side faces contiguous with the front and in that the cover and the housing between said side faces of the cover and said side faces of the housing comprise mating guide portions for slidably guiding the cover on the housing between the closed position and the intermediate position and for allowing of the pivoting option of the cover relative to the housing in the intermediate position.

A following embodiment of the invention is characterized in that the cover in closed position leaves at least one control key uncovered. With this construction it is possible to cover control keys having, for example, critical double functions, whereas at the same time several control keys continue to be accessible, for example, for responding to an incoming call, selecting menu functions, etc. Preferably, the uncovered control keys are located at maximum distance from the pivot axis of the cover.

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter.

In the drawings:

Fig. 1 is a front elevation of the telephone according to the invention, with a closed cover,

Fig. 2 is a bottom elevation of the telephone in the position of Fig. 1,

Fig. 3 is a side elevation of the telephone shown in Figs. 1 and 2, with a closed cover,

Fig. 4 is a side elevation as in Fig. 3, with the cover slid open to near to the intermediate position, and

Fig. 5 is a side elevation as in Figs. 3 and 4, in which the cover is swung open from the intermediate position.

The Figures show a telephone 1 with a housing 3 which comprises a plurality of control keys 5 at the front. This relates to a portable wireless telephone which customarily comprises an antenna 7, a loudspeaker 9, an LCD display 11 and a microphone 13. The telephone 1 shows at the front a cover 15 that can be moved between the closed position shown in Figs. 1, 2 and 3, in which said control keys 5 are covered, and an open position shown in Fig. 5 swung open around a pivot axis 17 near to an edge 19 of the

housing 3. In the latter position, the control keys 5 are accessible for control and the cover 15 and the housing 3 include an angle of approximately 90°. According to the invention, the cover 15 is slidable parallel to the housing 3 between said closed position and an intermediate position, see particularly Figs. 3 and 4. The cover can be swung open to the open position 5 shown in Fig. 5 starting from a slightly further intermediate position than shown in Fig. 4. In the latter position, the control keys 5 are freely accessible.

The cover 15 has a main portion 21 which, in closed position, runs parallel to the front 23 of the housing 3, see particularly Fig. 3. Furthermore, the cover 15 has side portions 25.1 and 25.2 forming extensions to the side edges of the main part 21 10 which, in closed position, are located near to the side faces 27.1 and 27.2 respectively of the housing, which side faces are adjacent the front 23 of the housing. Between said side portions 25.1. and 25.2 of the cover and said side faces 27.1 and 27.2 of the housing, the cover 15 and the housing 3 comprise mating guide portions for slidably guiding the cover 15 15 on the housing 3 between the closed position shown in Figs. 1, 2 and 3 and the intermediate position near to the position shown in Fig. 4, and also for allowing the cover 15 to pivot relative to the housing 3 in the intermediate position, to reach the open position shown in Fig. 5.

Said guide portions for slidably guiding the cover 15 comprise, for example, a number of ridges and slots of the housing. In the Figs. 4 and 5, a slot 29 can be 20 observed which is bounded on either end by ridges 31, 33 respectively, which lie slightly below the surface of the further adjacent part of the side face 27.2 of the housing. Either side portion of the cover 15 comprises on the inside protrusions which mate with said slots and ridges. In Figs. 3-5, these protrusions are symbolically shown by reference numerals 35 and 37, respectively. In the closed position shown in Fig. 3, the two protrusions 35, 37 25 respectively rest on the ridges 31, 33, respectively. Due to the elastic properties of the cover 15, which will generally be manufactured of a flexible plastic, the protrusions rest on the ridges while clamping, so that the cover is kept in place sufficiently firmly. In the position of Fig. 5, the protrusion 35 has reached the end of the ridge 33, so that the axis of the protrusion 35 coincides with the pivot axis 17 and the flap 15 can be swung to its position 30 shown in Fig. 5.

In closed position, see particularly Fig. 1, a number of control keys 39 are left uncovered. The more critical control keys 5 are covered by the flap 15. The latter keys have double functions and inadvertently depressing them could lead to needless activation of the telephone. The control keys 39, on the other hand, may also be used for

switching the telephone on and off, up and down scrolling on the LCD display 11, terminating the display on the LCD display 11 or controlling the menu functions of the telephone even when the cover is in closed position. In this manner, even when the cover 15 is closed, it remains possible to respond to and terminate an incoming call, and to use the preprogrammed menu functions, for example, for searching for a preprogrammed telephone number and dialling that number. The microphone 13 of the telephone is not covered when the flap is in closed position. In the main portion 21, the cover has an opening 41 which is located opposite the microphone 13 when the cover is closed. Obviously, when the telephone is used with the cover swung open, the microphone is also uncovered.

10 The positioning of the control keys 5 and 39 and the modelling of the cover 15 are such that the uncovered control keys 39 are most remote from the pivot axis 17 of the cover 15 and are not covered when the flap is in closed position.

 Although the invention has been explained above with reference to only a single embodiment, the invention is nonetheless not restricted thereto. Within the scope of
15 the appended claims, a great many different embodiments are possible for telephones having a cover which can both be slid and swung open. The cover 15, for example, could not have side portions 25.1, 25.2 which engage in the grooves of the housing side faces 27.1 and 27.2 respectively, but may be arranged such that housing sides engage in grooves of side faces of the cover. The top 43 of the cover 15 could have a profile, so that the sides 25.1 and 25.2
20 could be positioned over a larger distance alongside the side faces 27.1 and 27.2 of the housing 3 of the telephone and nevertheless leave the control keys 39 uncovered in closed position of the flap. In the main portion 21, the flap 15 could have openings for accessing certain control keys from the exterior while the flap is in closed position. In addition to said differences, there are many more differences possible within the scope of the appended
25 claims.

LIST OF REFERENCE NUMBERS

	1	- telephone
5	3	- housing
	5	- control keys
	7	- antenna
	9	- loudspeaker
	11	- LCD-display
10	13	- microphone
	15	- cover
	17	- pivot axis
	19	- edge
	21	- main portion
15	23	- front of housing
	25.1-25.2	- side portions of cover
	27.1-27.2	- side faces of housing
	29	- slot
	31-33	- ridges
20	35-37	- protrusions
	39	- protection keys
	41	- opening
	43	- top of cover

Claims:

1. A telephone with a housing that comprises a plurality of coverable control keys at the front and a cover (15) movable between a closed position in which said control keys are covered and an open position in which the cover is flapped down around a pivot axis (17) near to an edge (19) of the housing (9), in which open position said control keys
5 (5) are accessible for operation, characterized in that the cover (15) can be moved parallel to a housing (3) between said closed position and an intermediate position and in that the cover (15) can be pivoted around said pivot axis (17) between the intermediate position and the open position.
2. A telephone as claimed in claim 1, characterized in that the cover (15) in
10 closed position comprises a main portion (21) positioned substantially parallel to the front (23) of the housing (3), and also side portions contiguous with the main portion near to the side edges (25.1-25.2), which side portions in closed position are located adjacent housing side faces (27.1-27.2) contiguous with the front (23) and in that the cover (15) and the housing (3) between said side faces (25.1-25.3) of the cover and said side faces (27.1-27.2)
15 of the housing comprise mating guide portions for slidably guiding the cover (15) on the housing (3) between the closed position and the intermediate position and for allowing the pivoting option of the cover (15) relative to the housing (3) in the intermediate position.
3. A telephone as claimed in claim 1 or 2, characterized in that the cover (15) in closed position leaves at least one control key (39) uncovered.
- 20 4. A telephone as claimed in claim 3, characterized in that the uncovered control key(s) (39) is(are) at maximum distance from the pivot axis (17) of the cover (15).

1/4




FIG. 1




FIG. 2

2/4




FIG. 3

3/4




FIG. 4

4/4




FIG. 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 97/01444

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04M 1/04, H04M 1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04B, H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2289595 A (NEC CORPORATION (INCORPORATED IN JAPAN)), 22 November 1995 (22.11.95), figure 4B, abstract --	1-4
A	EP 0492748 A2 (MANNESMANN AKTIENGESELLSCHAFT), 1 July 1992 (01.07.92), column 2, line 31 - column 3, line 9, figures 1-2, abstract --	1-4
A	DE 4307164 A1 (CONSTIN DESIGN GMBH), 8 Sept 1994 (08.09.94), column 2, line 43 - column 4, line 18, figures 1-9B -- -----	1-4

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 April 1998

Date of mailing of the international search report

28.04.98

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Roland Landström

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/04/98

International application No.
PCT/IB 97/01444

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2289595 A	22/11/95	GB 9510041 D JP 2595932 B JP 7312631 A US 5657370 A	00/00/00 02/04/97 28/11/95 12/08/97
EP 0492748 A2	01/07/92	DE 4041988 A JP 4276957 A	02/07/92 02/10/92
DE 4307164 A1	08/09/94	NONE	